

Specifications

NKLC9-3-R

- * NKLC9-3-R is a rectangle 3-segment no hole column, perfect for a wide range of different desk applications.
- * It is an upside down column, where the smallest tube is mounted on the foot construction, which is intended for desks without crossbar. This feature ensures an optimum freedom of design
- * The function of anti-collision minimize the risk of damages when desk collision with an obstacle
- * NKLC9-3-R is compatible with all the standard NAKIN control boxes, and ensures a very low and pleasant noise level, and steady movement. Furthermore, the system has a very low standby power consumption less than 0.1W
- * Rectangle lifting column with 3mm optimised motor housing design and triangular support for extra strength and stability
- * The tube is no hole design
- * Max. load capacity is 800N per column
- * Fit with NKCB11-14 series control boxes to realize max speed 35mm/s
- * Low noise level <50dB
- * Max. Bending moment: 150N.m
- * Standard installation length: 560mm
- * Standard stroke length: 650mm
- * Column dimensions: outer tube:80x50mm; middle tube:75x45mm; inner tube:70x40mm
- * Motor housing dimension: 176x96x46mm
- * Motor: Self made high power motor
- * Hall sensor enabling parallel drive
- * Color: White, Black, Grey
- * Optional: Customized colors; Compatible with several different styles of feet; PVC-free column
- * Duty Cycle: 10%, max 2min continuous use, rest 18 minutes
- * Operating Temperature: -10°C~+70°C



Dimensions

